

Thermodur

All-purpose emulsion polish

- ▲ Self-shining polymer emulsion
- ▲ Outstanding film-forming properties
- ▲ Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- ▲ Very good water resistance
- ▲ Resistant to surface disinfectant products



Area of application

Can be used on water-resistant, coatable, stripped floorings, e.g. PVC, rubber, linoleum, absorbent natural and artificial stone. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Coating:

Depending on the absorbency of the surface, 2–3 layers at intervals of approx. 30 minutes.

Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer.

Consumption: 25.0 ml/m² per application.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, resins, softeners, preservatives.
pH value (concentrate): approx. 8.5